

# ADVENTURO ATX

ON / OFF ROAD ALL-TERRAIN

30 DAY

Test Drive

15 - 18 / 20 Inch 

Speed Rating: R / S / T / H 

55 - 80 Series 

UTQG: 520 A B 

M+S Rated 

50k

Limited  
Warranty



3PMS



Handling



Comfort



On / Off Road



Road Hazard  
Warranty

24HR

Roadside  
Assistance

The Adventuro ATX offers excellent balance between on and off road performance. With a Three-Peak Mountain Snowflake (3PMS) rating, the ATX is your solution for improved traction in winter conditions. The sidewall cleats and stair step grooves are designed to deliver premium off-road performance, while a cut and chip resistant compound ensures the integrity of the tread is not compromised. The Adventuro ATX—aggressively refined.

## FEATURES / BENEFITS

### Sidewall Cleats

Additional grip in deep soil and on loose surfaces

### Interlocked Center Rib

Dependable on-road handling and stability

### Wide Shoulder Channels

Improved performance on wet roads

### Stair Step Grooves

Enhanced off-road traction

### Three-Peak Mountain Snowflake (3PMS) Rating

Improved snow traction over a standard all-season rated tire



ON / OFF ROAD ALL-TERRAIN **ADVENTURO ATX**

Tire Size	LI / SR	UTQG	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
P235/75R15	108S XL	520 A B	100UA3700	6.5	6.0 - 8.0	2,183	50	13	29.1	9.5	30.2	BSW
P235/70R16	104T	520 A B	100UA3723	7.0	6.0 - 8.0	1,984	44	13	29.2	9.6	29.9	BSW
P245/70R16	106T	520 A B	100UA3724	7.0	6.5 - 8.0	2,094	44	13	29.8	9.8	31.8	BSW
P255/70R16	109T	520 A B	100UA3725	7.5	6.5 - 8.5	2,271	44	13	30.3	10.2	34.9	BSW
P265/70R16	111T	520 A B	100UA3702	8.0	7.0 - 9.0	2,403	44	13	30.9	10.7	36.4	BSW
P245/75R16	109T	520 A B	100UA3701	7.0	6.0 - 8.0	2,271	44	13	30.8	10.0	34.1	BSW
P265/75R16	114T	520 A B	100UA3726	7.5	7.0 - 9.0	2,601	44	13	31.9	10.6	37.1	BSW
P245/65R17	105T	520 A B	100UA3704	7.0	7.0 - 8.5	2,039	44	13	29.8	9.6	31.2	BSW
P265/70R17	113T	520 A B	100UA3706	8.0	7.0 - 9.0	2,535	44	13	31.9	10.8	38.3	BSW
265/60R18	110H	520 A B	100UA3707	8.0	7.5 - 9.5	2,337	44	13	30.7	10.7	36.1	BSW
265/65R18	114T	520 A B	100UA3708	8.0	7.5 - 9.5	2,601	44	13	31.8	10.6	38.4	BSW
275/65R18	116T	520 A B	AS151	8.0	7.5 - 9.5	2,756	44	13	32.1	11.0	39.2	BSW
P275/55R20	111H	520 A B	100UA3711	8.5	7.5 - 9.5	2,403	44	13	32.2	11.2	40.0	BSW
P275/60R20	114H	520 A B	100UA3727	8.0	7.5 - 9.5	1,180	44	13	33.0	11.0	40.9	BSW

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim inch	Rim Width Range inch	Max. Load (s/d) lbs	Max. Pressure psi	Tread Depth 32nd	Overall Diameter inch	Section Width inch	Weight lbs	Side Wall
31x10.50R15	109S	C / 6	AS154	8.5	7.0 - 9.0	2,270	50	16	30.5	10.6	40.9	OWL
LT245/75R16	120/116S	E / 10	AS153	7.0	6.5 - 8.0	3,042/2,778	80	16	30.5	9.8	42.7	OWL
LT265/75R16	123/120S	E / 10	AS152	7.5	7.0 - 8.0	3,415/3,085	80	16	31.7	10.5	48.5	OWL
LT285/75R16	126/123R	E / 10	AS155	8.0	7.5 - 9.0	3,750/3,415	80	16	32.8	11.3	51.4	OWL
LT265/70R17	121/118S	E / 10	AS150	8.0	7.0 - 8.5	3,195/2,910	80	16	31.7	10.7	48.1	OWL
LT285/70R17	121/118S	E / 10	AS158	8.5	7.5 - 9.0	3,195/2,910	80	16	32.8	11.5	52.8	OWL
LT245/75R17	121/118S	E / 10	AS156	7.0	6.5 - 7.5	3,195/2,910	80	16	31.5	9.8	46.1	OWL
LT235/80R17	120/117S	E / 10	AS157	6.5	6.0 - 7.5	3,085/2,835	80	16	31.8	9.3	44.0	OWL
LT275/65R18	123/120S	E / 10	AS159	8.0	7.5 - 9.0	3,415/3,085	80	16	32.1	11.0	49.9	OWL
LT265/70R18	124/121S	E / 10	AS160	8.0	7.0 - 9.0	3,525/3,195	80	16	32.6	10.5	52.3	OWL
LT275/70R18	125/122S	E / 10	AS161	8.0	7.0 - 8.5	3,640/3,305	80	16	33.2	11.0	52.0	OWL
LT275/65R20	126/123S	E / 10	AS162	8.0	7.5 - 9.5	3,750/3,415	80	16	34.1	10.5	59.5	OWL
35x12.50R20LT	121R	E / 10	AS163	10.0	8.5 - 11.0	3,195	65	16	34.5	12.5	64.8	OWL

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall OWL Outline White Letter